

FRAME PROFILES

Fire Rated "Slide-in" Frames for Speedpanel walls

Frame "Slide In" Profiles for Pyropanel Doors in Speedpanel Walls:

WALL TH. FRL	NB: All circled dimensions are for 13mm p/brd each side of wall. Will vary for different wall coverings.	
	Type A (edge fixed) Steel Thickness 1.2mm-1.4mm	Type B (face fixed) Steel Thickness 1.4mm-1.6mm
Wall: 51mm FRL: -/60/30	Profile: FSP51A 	Profile: FSP51B
Wall: 64mm FRL: -/90/30	Profile: FSP64A 	Profile: FSP64B
Wall: 78mm FRL: -/120/30	Profile: FSP78A 	Profile: FSP78B

FRAME PROFILES

Fire Rated "Built-in" Frames for Speedpanel walls

Frame "Built In" Profiles for Pyropanel Doors in Speedpanel Walls:

WALL TH. FRL	NB: All circled dimensions are for 13mm p'brd each side of wall. Will vary for different wall coverings.	
	Type C fixing	Type D fixing
	Steel Thickness: 1.4mm	Steel Thickness: 1.4mm
Wall: 51mm FRL: -/60/30	Profile: FSP51C 	Profile: FSP51D
Wall: 64mm FRL: -/90/30	Profile: FSP64C 	Profile: FSP64D
Wall: 78mm FRL: -/120/30	Profile: FSP78C 	Profile: FSP78D

HOW TO SPECIFY

"Door frame to be a Pyropanel FSP78B* Prime painted pressed metal door frame. Builder to confirm door frame applicability".

*Denotes example - change to suit requirements

Pyropanel Developments Pty Ltd

Unit 1, 97 Lewis Rd, Wantirna South, Vic 3152

Ph: (03) 9837 8500 Fax: (03) 9837 8550

Email: sales@pyropanel.com.au

Web: www.pyropanel.com.au

Distributed by: